



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

ISOPROPANOL 70-100%

Version 7.0

Print Date 2020/04/02

Revision date / valid from 2020/04/02

MSDS code: MIPA099

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : ISOPROPANOL 70-100%

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Identified use: See table in front of appendix for a complete overview of identified uses.

Uses advised against : At this moment we have not identified any uses advised against

1.3. Details of the supplier of the safety data sheet

Company : The Soap Kitchen
Unit 8 Caddsdwn Industrial Park
Clovelly Road, Bideford, EX39 3DX

1.4. Emergency telephone number

Emergency telephone number : Emergency only telephone number (open 24 hours):
+44 (0) 1865 407333 (N.C.E.C. Culham)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

REGULATION (EC) No 1272/2008			
Hazard class	Hazard category	Target Organs	Hazard statements
Flammable liquids	Category 2	---	H225
Serious eye damage/eye irritation	Category 2	---	H319
Specific target organ toxicity - single exposure	Category 3	---	H336

ISOPROPANOL 70-100%



For the full text of the H-Statements mentioned in this Section, see Section 16.

Most important adverse effects

Human Health	:	See section 11 for toxicological information.
Physical and chemical hazards	:	See section 9/10 for physicochemical information.
Potential environmental effects	:	See section 12 for environmental information.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard symbols	:	 
Signal word	:	Danger
Hazard statements	:	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements		
Prevention	:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing mist/vapours. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response	:	P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

ISOPROPANOL 70-100%

		P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
		P312	Call a POISON CENTER/doctor if you feel unwell.
		P331	Do NOT induce vomiting.
		P337 + P313	If eye irritation persists: Get medical advice/attention.
		P370 + P378	In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO ₂) to extinguish.
Storage	:	P403 + P235 P405	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	:	P501	Dispose of contents/ container in accordance with the local regulations.

Hazardous components which must be listed on the label:

- propan-2-ol

2.3. Other hazards

For Results of PBT and vPvB assessment see section 12.5.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components		Classification (REGULATION (EC) No 1272/2008)	
		Hazard class / Hazard category	Hazard statements
propan-2-ol			
Index-No.	: 603-117-00-0	>= 70 - <= 100	Flam. Liq.2
CAS-No.	: 67-63-0		Eye Irrit.2
EC-No.	: 200-661-7		STOT SE3
EU REACH- Reg. No.	: 01-2119457558-25-xxxx		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

ISOPROPANOL 70-100%

General advice	: Take off all contaminated clothing immediately. Wash contaminated clothing before re-use.
If inhaled	: Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position. Call a physician immediately. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance.
In case of skin contact	: Wash off immediately with plenty of water. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.
In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult an eye specialist immediately. Go to an ophthalmic hospital if possible.
If swallowed	: Rinse mouth with water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician immediately. If a person vomits when lying on his back, place him in the recovery position.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	: See Section 11 for more detailed information on health effects and symptoms.
Effects	: See Section 11 for more detailed information on health effects and symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment	: Treat symptomatically.
-----------	--------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	: High volume water jet

5.2. Special hazards arising from the substance or mixture

Specific hazards during firefighting	: The vapour may be invisible, heavier than air and spread along ground. Vapours may form explosive mixtures with air. Flash back possible over considerable distance. Heating or fire can release toxic gas. Highly flammable liquid and vapour.
Hazardous combustion products	: Carbon dioxide (CO ₂), Carbon monoxide, Smoke

ISOPROPANOL 70-100%

5.3. Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Wear personal protective equipment.
- Further advice : Cool closed containers exposed to fire with water spray. Heating will cause a pressure rise - with risk of bursting. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment. Keep away unprotected persons. Provide adequate ventilation. Keep away from heat and sources of ignition. Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist.

6.2. Environmental precautions

- Environmental precautions : Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3. Methods and materials for containment and cleaning up

- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Stop the leakage if it can be done without danger. Absorb with liquid-binding material (sand, diatomite, universal binders).
- Further information : Treat recovered material as described in the section "Disposal considerations".

6.4. Reference to other sections

- See Section 1 for emergency contact information.
See Section 8 for information on personal protective equipment.
See Section 13 for waste treatment information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Advice on safe handling : Keep container tightly closed. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Emergency eye wash fountains and emergency showers should be available in the immediate vicinity. Remove all sources of ignition.

ISOPROPANOL 70-100%

Hygiene measures : Keep away from food, drink and animal feedingstuffs. Smoking, eating and drinking should be prohibited in the application area. Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep in an area equipped with solvent resistant flooring.

Advice on protection against fire and explosion : Combustible liquid. Keep away from sources of ignition - No smoking. The vapour may be invisible, heavier than air and spread along ground. Vapours may form explosive mixtures with air. Take measures to prevent the build up of electrostatic charge. Use only in an area containing explosion proof equipment. Ensure all equipment is electrically grounded before beginning transfer operations.

Further information on storage conditions : Keep tightly closed in a dry and cool place. Keep in a well-ventilated place. Keep away from heat. Storage containers should be earthed and bonded to prevent accumulation of static charge.

Advice on common storage : Keep away from food, drink and animal feedingstuffs. Incompatible with oxidizing agents. Do not store together with oxidizing and self-igniting products.

Suitable packaging materials : Stainless steel, Carbon steel, Polyester, Teflon, Polyethylene

7.3. Specific end use(s)

Specific use(s) : No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Component:	propan-2-ol	CAS-No. 67-63-0
Derived No Effect Level (DNEL)/Derived Minimal Effect Level (DMEL)		

DNEL

Workers, Long-term - systemic effects, Skin contact : 888 mg/kg bw/day

DNEL

Workers, Long-term - systemic effects, Inhalation : 500 mg/m3

DNEL

Consumers, Long-term - systemic effects, Skin contact : 319 mg/kg bw/day

ISOPROPANOL 70-100%

DNEL

Consumers, Long-term - systemic effects, Inhalation : 89 mg/m³

DNEL

Consumers, Long-term - systemic effects, Ingestion : 26 mg/kg bw/day

Predicted No Effect Concentration (PNEC)

Fresh water	: 140.9 mg/l
Marine water	: 140.9 mg/l
Intermittent releases	: 140.9 mg/l
Sewage treatment plant (STP)	: 2251 mg/l
Sediment	: 552 mg/kg d.w.
Soil	: 28 mg/kg
Secondary poisoning	: 160 mg/kg food

Other Occupational Exposure Limit Values

UK. EH40 Workplace Exposure Limits (WELs), as amended, Short Term Exposure Limit (STEL):

500 ppm, 1,250 mg/m³

UK. EH40 Workplace Exposure Limits (WELs), as amended, Time Weighted Average (TWA):

400 ppm, 999 mg/m³

ELV (IE), Skin designation:

Can be absorbed through the skin.

ELV (IE), Time Weighted Average (TWA):

200 ppm

8.2. Exposure controls

Appropriate engineering controls

Refer to protective measures listed in sections 7 and 8.

Provide sufficient air exchange and/or exhaust in work rooms.

Take measures to prevent the build up of electrostatic charge.

Personal protective equipment

Respiratory protection

ISOPROPANOL 70-100%

Advice : If ventilation is insufficient, suitable respiratory protection must be provided
Required, if exposure limit is exceeded (e.g. OEL).
In the case of vapour formation use a respirator with an approved filter.

Filter Type : Recommended Filter type:A
Organic vapour type

Hand protection

Advice : The glove material has to be impermeable and resistant to the product / the substance / the preparation.
As the product is a mixture of several substances, the durability of the glove materials cannot be calculated in advance and has to be tested before use.
Protective gloves should be replaced at first signs of wear.
Protective gloves complying with EN 374.

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0.38 mm

Eye protection

Advice : Tightly fitting safety goggles
Ensure that eyewash stations and safety showers are close to the workstation location.
Equipment should conform to EN 166

Skin and body protection

Advice : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Wear appropriate chemical resistant clothing and boots.
Solvent resistant protective clothing

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.
Avoid subsoil penetration.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form : liquid
Colour : colourless
clear
Odour : alcohol-like

ISOPROPANOL 70-100%

Odour Threshold	: no data available
pH	: no data available
Freezing point	: no data available
Boiling point/boiling range	: 82 °C (ASTM D1078)
Flash point	: 12 °C (Method: ASTM D 56)
Evaporation rate	: 4 (Butyl Acetate = 1)
Flammability (solid, gas)	: no data available
Upper explosion limit	: 13 %(V)
Lower explosion limit	: 2 %(V)
Vapour pressure	: 4 kPa (20 °C)
Relative vapour density	: no data available
Relative density	: 0.79 (15 °C)
Water solubility	: completely miscible
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: 399 °C (ASTM E 659)
Thermal decomposition	: no data available
Viscosity, kinematic	: 1.8 mm ² /s (40 °C) 3.1 mm ² /s (20 °C)
Explosive properties	: EU legislation: Not explosive
Explosivity	: Formation of explosive air/vapour mixtures is possible.
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2. Other information

Molecular weight	: 60 g/mol
Bulk density	: 790 kg/m ³

SECTION 10: Stability and reactivity

10.1. Reactivity

ISOPROPANOL 70-100%

Advice : See sub-sections below.

10.2. Chemical stability

Advice : Under normal storage conditions peroxides may accumulate and explode when subjected to heat or shock. Distillation or evaporation increases peroxide formation and increases the explosion hazard.

10.3. Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur.

10.4. Conditions to avoid

Conditions to avoid : Keep away from heat and sources of ignition. Heat, flames and sparks.

10.5. Incompatible materials

Materials to avoid : Aldehydes, alkanolamines, Amines, Caustics agents, Chlorinated hydrocarbons. Strong oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products : Carbon oxides, Smoke, Material does not decompose at ambient temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Data for the product

Acute toxicity

Oral

Please find this information in the listing of the component/components below in this section.

Inhalation

Please find this information in the listing of the component/components below in this section.

Dermal

Please find this information in the listing of the component/components below in this section.

Irritation

Skin

Result : Please find this information in the listing of the component/components below in this section.

ISOPROPANOL 70-100%

Eyes

Result : Causes serious eye irritation.

Sensitisation

Result : Please find this information in the listing of the component/components below in this section.

CMR effects

CMR Properties

Carcinogenicity : Please find this information in the listing of the component/components below in this section.
Mutagenicity : Please find this information in the listing of the component/components below in this section.
Teratogenicity : Please find this information in the listing of the component/components below in this section.
Reproductive toxicity : Please find this information in the listing of the component/components below in this section.

Specific Target Organ Toxicity

Single exposure

Inhalation : May cause drowsiness or dizziness.

Repeated exposure

Remarks : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Other toxic properties

Repeated dose toxicity

no data available

Aspiration hazard

No aspiration toxicity classification,

Further information

Other relevant toxicity information : Prolonged skin contact may defat the skin and produce dermatitis.
Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Risk of product entering the lungs on vomiting after ingestion.
Liver injury may occur.

Component: propan-2-ol **CAS-No.** 67-63-0

Acute toxicity

Oral

ISOPROPANOL 70-100%

LD50 : 5840 mg/kg (Rat) (OECD Test Guideline 401)

Inhalation

LC50 : > 25 mg/l (Rat; 6 h; vapour) (OECD Test Guideline 403)

Dermal

LD50 : 13900 mg/kg (Rabbit) (OECD Test Guideline 402)

Irritation

Skin

Result : No skin irritation (OECD Test Guideline 404) Decreases the skin which may cause dry and rough. Prolonged or repeated skin contact may result in dermatitis.

Eyes

Result : Eye irritation (OECD - Guideline 405) Splashes in eyes may cause strong pain. Vapour acts irritant.

Sensitisation

Result : not sensitizing (Buehler Test; Dermal; Guinea pig) (OECD Test Guideline 406)

CMR effects

CMR Properties

Carcinogenicity : Based on available data, the classification criteria are not met.
Mutagenicity : In vitro tests did not show mutagenic effects
In vivo tests did not show mutagenic effects
Teratogenicity : No effects on or via lactation
Reproductive toxicity : Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity

Single exposure

Inhalation : Target Organs: Central nervous system May cause drowsiness or dizziness.

Repeated exposure

Remarks : Oral and inhalation repeated exposure studies demonstrated target

ISOPROPANOL 70-100%

organ effects in male rats (kidney) and male and female mice (thyroid) by mechanisms of action that are not relevant to humans

Other toxic properties

Aspiration hazard

Aspiration hazard if swallowed - can enter lungs and cause damage.
Aspiration may cause pulmonary oedema and pneumonitis.
Based on available data, the classification criteria are not met.,

SECTION 12: Ecological information

12.1. Toxicity

Data for the product

Acute toxicity

Short-term (acute) aquatic hazard

Result : Not expected to be harmful to aquatic organisms.

Component:

propan-2-ol

CAS-No. 67-63-0

Acute toxicity

Fish

LC50 : 9,640 mg/l (Pimephales promelas; 96 h) (flow-through test; OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

LC50 : 9,714 mg/l (Daphnia magna; 24 h) (static test; OECD Test Guideline 202)

algae

EC50 : > 100 mg/l (Scenedesmus subspicatus; 72 h)
LOEC 1000 mg/l (algae; 8 d)

Bacteria

EC50 : > 100 mg/l (Bacteria) no harming action

ISOPROPANOL 70-100%

12.2. Persistence and degradability

Component:	propan-2-ol	CAS-No. 67-63-0
Persistence and degradability		
Persistence		
Result	:	Transformation due to hydrolysis not expected to be significant. Transformation due to photolysis not expected to be significant.
Biodegradability		
Result	:	53 % (aerobic; domestic sewage; Related to: O2 consumption; Exposure Time: 5 d)(Directive 67/548/EEC, Annex V, C.5)Readily biodegradable.

12.3. Bioaccumulative potential

Component:	propan-2-ol	CAS-No. 67-63-0
Bioaccumulation		
Result	:	log Kow 0.05 Bioaccumulation is not expected.

12.4. Mobility in soil

Data for the product		
Mobility		
Result	:	Highly mobile in soils
Distribution among environmental compartments		
Soil	:	Koc: ca. 1.1,
Component:	propan-2-ol	CAS-No. 67-63-0
Mobility		
Water	:	The product is water soluble.
Soil	:	Mobile in soils

12.5. Results of PBT and vPvB assessment

Component:	propan-2-ol	CAS-No. 67-63-0
Results of PBT and vPvB assessment		

ISOPROPANOL 70-100%

Result : This substance is not considered to be persistent, bioaccumulating nor toxic (PBT)., This substance is not considered to be very persistent and very bioaccumulating (vPvB).

12.6. Other adverse effects

Data for the product

Additional ecological information

Result : Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : Disposal together with normal waste is not allowed. Special disposal required according to local regulations. Do not let product enter drains. Contact waste disposal services.

Contaminated packaging : Dispose of contaminated packaging in the same way as the product. In accordance with local and national regulations. Do not burn, or use a cutting torch on, the empty drum. Risk of explosion.

European Waste Catalogue Number : No waste code according to the European Waste Catalogue can be assigned for this product, as the intended use dictates the assignment. The waste code is established in consultation with the regional waste disposer.

SECTION 14: Transport information

14.1. UN number

1219

14.2. UN proper shipping name

ADR : ISOPROPANOL
RID : ISOPROPANOL
IMDG : ISOPROPANOL

14.3. Transport hazard class(es)

ADR-Class : 3
(Labels; Classification Code; Hazard Identification Number; Tunnel restriction code) 3; F1; 33; (D/E)

RID-Class : 3
(Labels; Classification Code; Hazard Identification Number) 3; F1; 33

ISOPROPANOL 70-100%

IMDG-Class : 3
(Labels; EmS) 3; F-E, S-D

14.4. Packaging group

ADR : II
RID : II
IMDG : II

14.5. Environmental hazards

Environmentally hazardous according to ADR : no
Environmentally hazardous according to RID : no
Marine Pollutant according to IMDG-Code : no

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IMDG : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Data for the product

Other regulations : Occupational restrictions: Take note of Dir 92/85/EEC on the safety and health of pregnant workers at work and of Dir 94/33/EC on the protection of young people at work.

Component:	propan-2-ol	CAS-No. 67-63-0
-------------------	--------------------	------------------------

EU. REACH, Annex XVII, : Point Nos.: , 3; Listed
Marketing and Use
Restrictions (Regulation
1907/2006/EC)

Point Nos.: , 40; Listed

EU. Regulation No : EC Number: , 200-661-7; Listed
1451/2007 [Biocides],
Annex I, OJ (L 325)

Notification status
propan-2-ol:

ISOPROPANOL 70-100%

Regulatory List	Notification	Notification number
AICS	YES	
DSL	YES	
EINECS	YES	200-661-7
ENCS (JP)	YES	(2)-207
IECSC	YES	
ISHL (JP)	YES	2-(8)-319
ISHL (JP)	YES	(2)-207
JEX (JP)	YES	(2)-207
KECI (KR)	YES	KE-29363
NZIOC	YES	HSR001180
PICCS (PH)	YES	
TSCA	YES	

15.2. Chemical safety assessment

no data available

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Abbreviations and Acronyms

BCF	bioconcentration factor
BOD	biochemical oxygen demand
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	carcinogenic, mutagenic or toxic to reproduction
COD	chemical oxygen demand
DNEL	derived no-effect level
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
LC50	median lethal concentration
LOAEC	lowest observed adverse effect concentration
LOAEL	lowest observed adverse effect level
LOEL	lowest observed effect level
NLP	no-longer polymer
NOAEC	no observed adverse effect concentration
NOAEL	no observed adverse effect level

ISOPROPANOL 70-100%

NOEC	no observed effect concentration
NOEL	no observed effect level
OECD	Organisation for Economic Cooperation and Development
OEL	occupational exposure limit
PBT	persistent, bioaccumulative and toxic
REACH Auth. No.:	REACH Authorisation Number
REACH AuthAppC. No.	REACH Authorisation Application Consultation Number
PNEC	predicted no-effect concentration
STOT	specific target organ toxicity
SVHC	substance of very high concern
UVCB	substance of unknown or variable composition, complex reaction products or biological materials
vPvB	very persistent and very bioaccumulative

Further information

Key literature references : Supplier information and data from the "Database of registered substances" of the European Chemicals Agency (ECHA) were used to create this safety data sheet.

Methods used for product classification : The classification for human health, physical and chemical hazards and environmental hazards were derived from a combination of calculation methods and if available test data.

Hints for trainings : The workers have to be trained regularly on the safe handling of the products based on the information provided in the Safety Data Sheet and the local conditions of the workplace. National regulations for the training of workers in the handling of hazardous materials must be adhered to.

Other information : The information provided in this Safety Data Sheet is correct to our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements and is not to be considered as a warranty or quality specification and does not constitute a legal relationship.

The information contained in this Safety Data Sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

|| Indicates updated section.

ISOPROPANOL 70-100%

No.	Short title	Main User Group (SU)	Sector of Use (SU)	Product Category (PC)	Process Category (PROC)	Environmental Release Category (ERC)	Article Category (AC)	Specified
1	Manufacture of substance	3	8, 9	NA	1, 2, 3, 4, 8a, 8b, 15	1, 4	NA	ES001
2	Distribution of substance	3	8, 9	NA	1, 2, 3, 4, 8a, 8b, 9, 15	1, 2, 3, 4, 5, 6a, 6b, 6c, 6d, 7	NA	ES005
3	Formulation & (re)packing of substances and mixtures	3	10	NA	1, 2, 3, 4, 5, 8a, 8b, 9, 14, 15	2	NA	ES007
4	Use in rubber production and processing	3	NA	NA	1, 2, 3, 4, 5, 6, 7, 8a, 8b, 9, 13, 14, 15, 21	1, 4, 6d	NA	ES029
5	Use in polymer processing	3	NA	NA	1, 2, 3, 4, 5, 6, 8a, 8b, 9, 13, 14, 21	4	NA	ES031
6	Use in polymer processing	22	NA	NA	1, 2, 6, 8a, 8b, 14, 21	8a, 8d	NA	ES069
7	Use in coatings	3	NA	NA	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 13, 14, 15	4	NA	ES009
8	Use in coatings	21	NA	1, 4, 8, 9a, 9b, 9c, 15, 18, 23, 24, 31, 34	NA	8a, 8d	NA	ES073
9	Use in coatings	22	NA	NA	1, 2, 3, 4, 5, 8a, 8b, 10, 11, 13, 15, 19	8a, 8d	NA	ES039
10	Use in cleaning agents	3	NA	NA	1, 2, 3, 4, 7, 8a, 8b, 10, 13	4	NA	ES011
11	Use in cleaning agents	21	NA	3, 4, 8, 9a, 24, 35, 38	NA	8a, 8d	NA	ES338
12	Use in cleaning agents	22	NA	NA	1, 2, 3, 4, 8a, 8b, 10, 11, 13	8a, 8d	NA	ES041
13	Use in binder and release agents	3	NA	NA	1, 2, 3, 4, 6, 7, 8b, 10, 14	4	NA	ES021
14	Use in binder and release agents	22	NA	NA	1, 2, 3, 4, 6, 8b, 10, 11, 14	8a, 8d	NA	ES047
15	Use in agrochemicals	21	NA	12, 27	NA	8a, 8d	NA	ES438
16	Use in agrochemicals	22	NA	NA	1, 2, 4, 8a, 8b, 11, 13	8a, 8d	NA	ES049
17	Use in fuel	3	NA	NA	1, 2, 3, 8a, 8b, 16	7	NA	ES023
18	Use in fuel	21	NA	13	NA	9a, 9b	NA	ES440

ISOPROPANOL 70-100%

19	Use in fuel	22	NA	NA	1, 2, 3, 8a, 8b, 16	9a, 9b	NA	ES051
20	Use as lubricants	3	NA	NA	1, 2, 3, 4, 7, 8a, 8b, 9, 10, 13, 17, 18	4, 7	NA	ES015
21	Use as lubricants	21	NA	1, 24, 31	NA	8a, 8d, 9a, 9b	NA	ES427
22	Use as lubricants	22	NA	NA	1, 2, 3, 4, 8a, 8b, 9, 10, 11, 13, 17, 18, 20	8a, 9a, 9b, 8d	NA	ES036
23	Use as Functional Fluids	3	NA	NA	1, 2, 4, 8a, 8b, 9	7	NA	ES025
24	Use as Functional Fluids	21	NA	16, 17	NA	9a, 9b	NA	ES449
25	Use as Functional Fluids	22	NA	NA	1, 2, 3, 8a, 9, 20	9a, 9b	NA	ES053
26	Use in laboratories	3	NA	NA	10, 15	2, 4	NA	ES027
27	Use in laboratories	22	NA	NA	10, 15	8a	NA	ES061
28	Use in metal working fluids / rolling oils	3	NA	NA	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 13, 17	4	NA	ES017
29	Use in metal working fluids / rolling oils	22	NA	NA	1, 2, 3, 8a, 8b, 9, 10, 11, 13, 17	8a, 8d	NA	ES045
30	Use in de-icing and anti-icing applications	21	NA	4	NA	8d	NA	ES453
31	Use in de-icing and anti-icing applications	22	NA	NA	1, 2, 8a, 8b, 11	8d	NA	ES055
32	Use as water treatment chemicals	3	NA	NA	1, 2, 3, 4, 8a, 8b, 13	3, 4	NA	ES033
33	Use as water treatment chemicals	21	NA	36, 37	NA	8f	NA	ES459
34	Use as water treatment chemicals	22	NA	NA	1, 3, 4, 8a, 8b, 13	8f	NA	ES071
35	Use in oil and gas field drilling and production operations	3	NA	NA	1, 2, 3, 4, 8a, 8b	4	NA	ES013
36	Use in explosives	22	NA	NA	1, 2, 3, 5, 8a, 8b	8d	NA	ES063
37	Other consumer uses	21	NA	28, 39	NA	8a, 8d	NA	ES457
38	Use as an intermediate	3	8, 9	NA	1, 2, 3, 4, 8a, 8b, 15	6a	NA	ES003
39	Use as blowing agents	3	NA	NA	1, 2, 3, 8b, 9, 12	4	NA	ES019
40	Use in road and construction applications	22	NA	NA	8a, 8b, 9, 10, 11, 13	8d, 8f	NA	ES059
41	Use as mining chemicals	3	NA	NA	1, 2, 3, 4, 5, 8a, 8b, 9	4	NA	ES037

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 1: Manufacture of substance

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU8: Manufacture of bulk, large scale chemicals (including petroleum products) SU9: Manufacture of fine chemicals
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC15: Use as laboratory reagent
Environmental Release Categories	ERC1: Manufacture of substances ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	General exposures (open systems)	Handle substance within a closed system.(PROC4)
	Bulk transfers Open systems	Handle substance within a closed system.(PROC8b)
	Bulk transfers Closed systems	Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling.(PROC8b)
	Equipment cleaning and maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle. Drain down system prior to equipment break-in or maintenance. Clear spills immediately.(PROC8a)
	Storage	Store substance within a closed system. Avoid dip sampling. Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).(PROC2)

ISOPROPANOL 70-100%

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection.
Avoid direct eye contact with product, also via contamination on hands.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15: ECETOC TRA worker v3

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	General exposures (closed systems)	Worker - inhalative, long-term - systemic	0.01ppm	0.00
PROC1	General exposures (closed systems)	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC2	General exposures (closed systems)	Worker - inhalative, long-term	10ppm	0.05
PROC2	General exposures (closed systems)	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00
PROC3	General exposures (closed systems)	Worker - inhalative, long-term	25ppm	0.12
PROC3	General exposures (closed systems)	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC4	General exposures (open systems)	Worker - inhalative, long-term	20ppm	0.10
PROC4	General exposures (open systems)	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC8b	Process sampling	Worker - inhalative, long-term	50ppm	0.25
PROC8b	Process sampling	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC15	Laboratory activities	Worker - inhalative, long-term	10ppm	0.05
PROC15	Laboratory activities	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC8b	Bulk transfers, Open systems	Worker - inhalative, long-term	150ppm	0.74
PROC8b	Bulk transfers, Open systems	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC8b	Bulk transfers, Closed systems	Worker - inhalative, long-term	2.5ppm	0.25
PROC8b	Bulk transfers, Closed systems	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC8a	Equipment cleaning and maintenance	Worker - inhalative, long-term	50ppm	0.25
PROC8a	Equipment cleaning and maintenance	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.02
PROC2	Storage	Worker - inhalative, long-term	10ppm	0.05
PROC2	Storage	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00

ISOPROPANOL 70-100%

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 2: Distribution of substance

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU8: Manufacture of bulk, large scale chemicals (including petroleum products) SU9: Manufacture of fine chemicals
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC15: Use as laboratory reagent
Environmental Release Categories	ERC1: Manufacture of substances ERC2: Formulation of preparations ERC3: Formulation in materials ERC4: Industrial use of processing aids in processes and products, not becoming part of articles ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates) ERC6b: Industrial use of reactive processing aids ERC6c: Industrial use of monomers for manufacture of thermoplastics ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers ERC7: Industrial use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	General exposures (open systems)	Clear transfer lines prior to de-coupling.(PROC4)
	Process sampling	Avoid dip sampling.(PROC3)
	Bulk transfers	Clear transfer lines prior to de-coupling.(PROC8b)

ISOPROPANOL 70-100%

	Open systems	
	Bulk transfers Closed systems	Clear transfer lines prior to de-coupling.(PROC8b)
	Drum and small package filling	Clear spills immediately. Put lids on containers immediately after use.(PROC9)
	Equipment cleaning and maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle. Drain down system prior to equipment break-in or maintenance. Apply vessel entry procedures including use of forced supplied air.(PROC8a)
	Storage	Store substance within a closed system. Avoid dip sampling.(PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation		Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15: ECETOC TRA worker v3

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	General exposures (closed systems)	Worker - inhalative, long-term	0.01ppm	0.000491
PROC1	General exposures (closed systems)	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.0015
PROC2	General exposures (closed systems)	Worker - inhalative, long-term	10ppm	0.05
PROC2	General exposures (closed systems)	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00
PROC3	General exposures (closed systems), Process sampling	Worker - inhalative, long-term	25ppm	0.12
PROC3	General exposures (closed systems), Process sampling	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC4	General exposures (open systems)	Worker - inhalative, long-term	20ppm	0.10
PROC4	General exposures (open systems)	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC15	Laboratory activities	Worker - inhalative, long-term	10ppm	0.05
PROC15	Laboratory activities	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC8b	Bulk transfers, Open systems	Worker - inhalative, long-term	50ppm	0.25
PROC8b	Bulk transfers, Open systems	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01

ISOPROPANOL 70-100%

PROC8b	Bulk transfers, Closed systems	Worker - inhalative, long-term	50ppm	0.25
PROC8b	Bulk transfers, Closed systems	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC9	Drum and small package filling	Worker - inhalative, long-term	50ppm	0.25
PROC9	Drum and small package filling	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC8a	Equipment cleaning and maintenance	Worker - inhalative, long-term	50ppm	0.25
PROC8a	Equipment cleaning and maintenance	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.02
PROC2	Storage	Worker - inhalative, long-term	10ppm	0.05
PROC2	Storage	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 3: Formulation & (re)packing of substances and mixtures

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p> <p>PROC15: Use as laboratory reagent</p>
Environmental Release Categories	ERC2: Formulation of preparations

2.1 Contributing scenario controlling environmental exposure for: ERC2

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	Process sampling	Avoid dip sampling.(PROC3)
	Bulk transfers	Clear transfer lines prior to de-coupling. Clear spills immediately. Remotely vent displaced vapours.(PROC8b)
	Drum and small package filling	Put lids on containers immediately after use.(PROC9)
	Equipment cleaning and maintenance	Apply vessel entry procedures including use of forced supplied air. Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.

ISOPROPANOL 70-100%

		Avoid dip sampling.(PROC2)		
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.			
	Avoid direct eye contact with product, also via contamination on hands.			
3. Exposure estimation and reference to its source				
Environment				
No exposure assessment presented for the environment.				
Workers				
PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15: ECETOC TRA worker v3				
Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	General exposures (closed systems)	Worker - inhalative, long-term	0.01ppm	0.00
PROC1	General exposures (closed systems)	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC2	General exposures (closed systems)	Worker - inhalative, long-term	10ppm	0.05
PROC2	General exposures (closed systems)	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00
PROC3	General exposures (closed systems)	Worker - inhalative, long-term	25ppm	0.12
PROC3	General exposures (closed systems)	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC4	General exposures (open systems)	Worker - inhalative, long-term	20ppm	0.10
PROC4	General exposures (open systems)	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC3	Batch processes at elevated temperatures	Worker - inhalative, long-term	100ppm	0.49
PROC3	Batch processes at elevated temperatures	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC3	Process sampling	Worker - inhalative, long-term	25ppm	0.12
PROC3	Process sampling	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC15	Laboratory activities	Worker - inhalative, long-term	10ppm	0.05
PROC15	Laboratory activities	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC8b	Bulk transfers	Worker - inhalative, long-term	50ppm	0.25
PROC8b	Bulk transfers	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC5	Mixing operations (open systems)	Worker - inhalative, long-term	50ppm	0.25
PROC5	Mixing operations (open systems)	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.02
PROC8a	Transfer from/pouring from containers, Manual	Worker - inhalative, long-term	50ppm	0.25
R56871 / Version 7.0				
28/130				
EN				

ISOPROPANOL 70-100%

PROC8a	Transfer from/pouring from containers, Manual	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.02
PROC8b	Drum/batch transfers	Worker - inhalative, long-term	50ppm	0.25
PROC8b	Drum/batch transfers	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC14	Production or preparation or articles by tableting, compression, extrusion or pelletisation	Worker - inhalative, long-term	50ppm	0.25
PROC14	Production or preparation or articles by tableting, compression, extrusion or pelletisation	Worker - dermal, long-term - systemic	3.43mg/kg/day	0.00
PROC9	Drum and small package filling	Worker - inhalative, long-term	50ppm	0.25
PROC9	Drum and small package filling	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC8a	Equipment cleaning and maintenance	Worker - inhalative, long-term	50ppm	0.25
PROC8a	Equipment cleaning and maintenance	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.02
PROC2	Storage	Worker - inhalative, long-term	10ppm	0.05
PROC2	Storage	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 4: Use in rubber production and processing

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)</p> <p>PROC6: Calendering operations</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p> <p>PROC15: Use as laboratory reagent</p> <p>PROC21: Low energy manipulation of substances bound in materials and/ or articles</p>
Environmental Release Categories	<p>ERC1: Manufacture of substances</p> <p>ERC4: Industrial use of processing aids in processes and products, not becoming part of articles</p> <p>ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers</p>

2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4, ERC6d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC21

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Material transfers	Handle substance within a closed system.(PROC8b)
	Calendering (including Banburys)	Minimise exposure by extracted full enclosure for the operation or equipment.(PROC6)
	Tyre build up	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.(PROC7)
	Vulcanisation	Minimise exposure by extracted full enclosure for

ISOPROPANOL 70-100%

		the operation or equipment.(PROC6)
	Vulcanisation	Provide extract ventilation to material transfer points and other openings.(PROC6)
	Cooling cured articles	Minimise exposure by extracted full enclosure for the operation or equipment.(PROC6)
	Storage	Store substance within a closed system.(PROC1, PROC2)

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 5: Use in polymer processing

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)</p> <p>PROC6: Calendering operations</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p> <p>PROC21: Low energy manipulation of substances bound in materials and/ or articles</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC21

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Handle substance within a closed system.(PROC8b)
	Bulk weighing	Handle substance within a closed system.(PROC1)
	Small scale weighing	Handle all packages and containers carefully to minimise spills.(PROC9)
	Additive premixing	Handle all packages and containers carefully to minimise spills.(PROC3, PROC4)
	Bulk transfers	Use dry break couplings for material transfer.(PROC8b, PROC9)
	Equipment maintenance	Clear up spills immediately and dispose of waste safely.(PROC8a)
	Storage	Store substance within a closed system.(PROC1,

ISOPROPANOL 70-100%

PROC2)

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 6: Use in polymer processing

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC6: Calendering operations PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation PROC21: Low energy manipulation of substances bound in materials and/ or articles
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC6, PROC8a, PROC8b, PROC14, PROC21

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Handle substance within a closed system.(PROC1, PROC2)
	Material transfers	Use bulk or semi-bulk handling systems.(PROC8b)
	Storage	Store substance within a closed system.(PROC1, PROC2)

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 7: Use in coatings

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p> <p>PROC15: Use as laboratory reagent</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1)
	General exposures (closed systems) With sample collection Use in contained systems	Handle substance within a closed system.(PROC2)
	Film formation - force drying (50 - 100°C). Stoving (>100°C). UV/EB radiation curing	Handle substance within a closed system.(PROC2)
	Mixing operations General exposures (closed systems)	Handle substance within a closed system.(PROC3)

ISOPROPANOL 70-100%

	Spraying (automatic/robotic)	Carry out in a vented booth provided with laminar airflow.(PROC7)		
	Manual Spraying	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).(PROC7)		
	Material transfers	Clear transfer lines prior to de-coupling.(PROC8a)		
	Material transfers	Clear transfer lines prior to de-coupling.(PROC8b)		
	Dipping, immersion and pouring	Avoid manual contact with wet work pieces.(PROC13)		
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.			
	Avoid direct eye contact with product, also via contamination on hands.			
3. Exposure estimation and reference to its source				
Environment				
No exposure assessment presented for the environment.				
Workers				
PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15: ECETOC TRA worker v3				
Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	General exposures (closed systems)	Worker - inhalative, long-term	0.01ppm	0.00
PROC1	General exposures (closed systems)	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC2	General exposures (closed systems), With sample collection	Worker - inhalative, long-term	10ppm	0.00
PROC2	General exposures (closed systems), With sample collection	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00
PROC2	Film formation - force drying (50 - 100°C). Stoving (>100°C). UV/EB radiation curing	Worker - inhalative, long-term	50ppm	0.2
PROC2	Film formation - force drying (50 - 100°C). Stoving (>100°C). UV/EB radiation curing	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00
PROC3	General exposures (closed systems)	Worker - inhalative, long-term	25ppm	0.1
PROC3	General exposures (closed systems)	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC4	Film formation - air drying	Worker - inhalative, long-term	20ppm	0.1
PROC4	Film formation - air drying	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.00
PROC5	Preparation of material for application, Mixing operations (open systems)	Worker - inhalative, long-term	50ppm	0.2
PROC5	Preparation of material for application, Mixing	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.00
R56871 / Version 7.0				
37/130				
EN				

ISOPROPANOL 70-100%

	operations (open systems)			
PROC7	Spraying (automatic/robotic)	Worker - inhalative, long-term	50ppm	0.2
PROC7	Spraying (automatic/robotic)	Worker - dermal, long-term - systemic	42.86mg/kg/day	0.00
PROC7	Manual spraying	Worker - inhalative, long-term	75ppm	0.4
PROC7	Manual spraying	Worker - dermal, long-term - systemic	42.86mg/kg/day	0.00
PROC8a	Material transfers	Worker - inhalative, long-term	75ppm	0.2
PROC8a	Material transfers	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.00
PROC8b	Material transfers	Worker - inhalative, long-term	50ppm	0.2
PROC8b	Material transfers	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.00
PROC10	Roller, spreader, flow application	Worker - inhalative, long-term	50ppm	0.2
PROC10	Roller, spreader, flow application	Worker - dermal, long-term - systemic	27.43mg/kg/day	0.00
PROC13	Dipping, immersion and pouring	Worker - inhalative, long-term	50ppm	0.2
PROC13	Dipping, immersion and pouring	Worker - dermal, long-term - systemic	0.69mg/kg/day	0.00
PROC15	Laboratory activities	Worker - inhalative, long-term	10ppm	0.00
PROC15	Laboratory activities	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC9	Material transfers, Drum/batch transfers, Transfer from/pouring from containers	Worker - inhalative, long-term	50ppm	0.2
PROC9	Material transfers, Drum/batch transfers, Transfer from/pouring from containers	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.00
PROC14	Production or preparation or articles by tableting, compression, extrusion or pelletisation	Worker - inhalative, long-term	50ppm	0.2
PROC14	Production or preparation or articles by tableting, compression, extrusion or pelletisation	Worker - dermal, long-term - systemic	3.43mg/kg/day	0.00

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>

ISOPROPANOL 70-100%

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 8: Use in coatings

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC1: Adhesives, sealants PC4: Anti-Freeze and de-icing products PC8: Biocidal products (e.g. Disinfectants, pest control) PC9a: Coatings and paints, thinners, paint removers PC9b: Fillers, putties, plasters, modelling clay PC9c: Finger paints PC15: Non-metal-surface treatment products PC18: Ink and toners PC23: Leather treatment products PC24: Lubricants, greases, release products PC31: Polishes and wax blends PC34: Textile dyes, finishing and impregnating products; including bleaches and other processing aids
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling consumer exposure for: PC1: Glues, hobby use

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	9 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC1: Glues DIY-use (carpet glue, tile glue, wood parquet glue)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	6390 g
Frequency and duration of use	Frequency of use	1 days/year

ISOPROPANOL 70-100%

	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 110 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.4 Contributing scenario controlling consumer exposure for: PC1: Glue from spray		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	85.05 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.5 Contributing scenario controlling consumer exposure for: PC1: Sealants		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	75 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g.		No specific risk management measure identified
R56871 / Version 7.0		
41/130		
EN		

ISOPROPANOL 70-100%

behavioural advice, personal protection and hygiene)	Consumer Measures	beyond those operational conditions stated.
--	-------------------	---

2.6 Contributing scenario controlling consumer exposure for: PC4: Washing car window

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.5 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.7 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2000 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.8 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa

ISOPROPANOL 70-100%

Amount used	Amount used per event	4 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 214.4 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.9 Contributing scenario controlling consumer exposure for: PC8: Cleaners, liquids

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 5%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	27 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.10 Contributing scenario controlling consumer exposure for: PC8: Cleaners, trigger sprays

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 15%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient	

ISOPROPANOL 70-100%

exposure	temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.11 Contributing scenario controlling consumer exposure for: PC9a: Solvent rich, high solid, water borne paint, PC15: Solvent rich, high solid, water borne paint		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 27,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	744 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428.75 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.12 Contributing scenario controlling consumer exposure for: PC9a: Aerosol spray can, PC15: Aerosol spray can		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	215 g
Frequency and duration of use	Frequency of use	2 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.13 Contributing scenario controlling consumer exposure for: PC9a: Removers (paint-, glue-, wall paper-, sealant-remover), PC15: Removers (paint-, glue-, wall paper-, sealant remover)		
Product characteristics	Concentration of the	Concentration of substance in product : 0% - 50%

ISOPROPANOL 70-100%

	Substance in Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	491 g
Frequency and duration of use	Frequency of use	3 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.14 Contributing scenario controlling consumer exposure for: PC9b: Fillers and putty

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	85 g
Frequency and duration of use	Frequency of use	12 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.15 Contributing scenario controlling consumer exposure for: PC9b: Plasters and floor equalizers

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	13800 g
Frequency and duration of use	Frequency of use	12 days/year

ISOPROPANOL 70-100%

	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.16 Contributing scenario controlling consumer exposure for: PC9b: Modelling clay		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	1 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 254.4 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.17 Contributing scenario controlling consumer exposure for: PC9c		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	1.35 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 254.4 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g.		Avoid using at a product concentration greater than
R56871 / Version 7.0		
46/130		
EN		

ISOPROPANOL 70-100%

behavioural advice, personal protection and hygiene)	Consumer Measures	15 %
2.18 Contributing scenario controlling consumer exposure for: PC18		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	40 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 71.40 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.19 Contributing scenario controlling consumer exposure for: PC23: Polishes, wax/cream (floor, furniture, shoes)		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	56 g
Frequency and duration of use	Frequency of use	29 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	73.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 430 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.20 Contributing scenario controlling consumer exposure for: PC23: Polishes, spray (furniture, shoes)		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
R56871 / Version 7.0		
47/130		
EN		

ISOPROPANOL 70-100%

	use)	
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	56 g
Frequency and duration of use	Frequency of use	8 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 430 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.21 Contributing scenario controlling consumer exposure for: PC24: Liquids

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2200 g
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.22 Contributing scenario controlling consumer exposure for: PC24: Pastes

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	34 g
Frequency and duration of use	Frequency of use	10 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by	Exposed skin area	Covers skin contact area up to 468 cm ²

ISOPROPANOL 70-100%

risk management	
Other given operational conditions affecting consumers exposure	Room size 20 m3 Covers use under typical household ventilation., Covers use at ambient temperatures.
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures No specific risk management measure identified beyond those operational conditions stated.

2.23 Contributing scenario controlling consumer exposure for: PC24: Sprays

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	73 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428.75 cm²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.24 Contributing scenario controlling consumer exposure for: PC31: Polishes, wax / cream (floor, furniture, shoes)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	142 g
Frequency and duration of use	Frequency of use	29 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	73.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 430 cm²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.25 Contributing scenario controlling consumer exposure for: PC31: Polishes, spray (furniture,

ISOPROPANOL 70-100%

shoes)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	8 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 430 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.26 Contributing scenario controlling consumer exposure for: PC34

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	115 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

PC34, PC1: Glues, hobby use, PC1: Glues DIY-use, PC1: Glue from spray, PC1: Sealants, PC4: Washing car window, PC4: Pouring into radiator, PC4: Lock de-icer, PC9a: Solvent rich, high solid, water borne paint, PC9a:

ISOPROPANOL 70-100%

Aerosol spray can, PC9a: Removers, PC15: Solventrich, high solid, water borne paint, PC15: Aerosol spray can, PC15: Removers, PC23: Polishes, wax/cream, PC23: Polishes, spray, PC31: Polishes, wax / cream, PC31: Polishes, spray, PC9b: Fillers and putty, PC9b: Plasters and floor equalizers, PC9b: Modelling clay,, ECETOC TRA worker v3

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PC1: Glues, hobby use	---	Consumer inhalation, long term	135mg/m ³	0.16
PC1: Glues, hobby use	---	Consumer dermal exposure	1.8mg/kg/day	0.01
PC1: Glues, hobby use	---	Consumer oral, long-term	0mg/kg/day	0.00
PC1: Glues DIY-use	---	Consumer inhalation, long term	225000mg/m ³	0.33
PC1: Glues DIY-use	---	Consumer dermal exposure	21.4mg/kg/day	0.00
PC1: Glues DIY-use	---	Consumer oral, long-term	0mg/kg/day	0.00
PC1: Glue from spray	---	Consumer inhalation, long term	3825mg/m ³	0.02
PC1: Glue from spray	---	Consumer dermal exposure	1.8mg/kg/day	0.00
PC1: Glue from spray	---	Consumer oral, long-term	0mg/kg/day	0.00
PC1: Sealants	---	Consumer inhalation, long term	5850mg/m ³	0.66
PC1: Sealants	---	Consumer dermal exposure	1.8mg/kg/day	0.01
PC1: Sealants	---	Consumer oral, long-term	0mg/kg/day	0.00
PC4: Washing car window	---	Consumer inhalation, long term	0.1mg/m ³	0.00
PC4: Washing car window	---	Consumer dermal exposure	0mg/kg/day	0.00
PC4: Washing car window	---	Consumer oral, long-term	0mg/kg/day	0.00
PC4: Pouring into radiator	---	Consumer inhalation, long term	5882.4mg/m ³	0.10
PC4: Pouring into radiator	---	Consumer dermal exposure	14.3mg/kg/day	0.11
PC4: Pouring into radiator	---	Consumer oral, long-term	0mg/kg/day	0.00
PC4: Lock de-icer	---	Consumer inhalation, long term	58.8mg/m ³	0.01
PC4: Lock de-icer	---	Consumer dermal exposure	17.9mg/kg/day	0.06
PC4: Lock de-icer	---	Consumer oral, long-term	0mg/kg/day	0.00
PC8: Cleaners, liquid	---	Consumer inhalation, long term	1500mg/m ³	0.00
PC8: Cleaners, liquid	---	Consumer dermal exposure	85.8mg/kg/day	0.00
PC8: Cleaners, liquid	---	Consumer oral, long-term	0mg/kg/day	0.08

ISOPROPANOL 70-100%

PC8: Cleaners, trigger sprays	---	Consumer inhalation, long term	6250mg/m ³	0.09
PC8: Cleaners, trigger sprays	---	Consumer dermal exposure	71.5mg/kg/day	0.22
PC8: Cleaners, trigger sprays	---	Consumer oral, long-term	0mg/kg/day	0.00
PC9a: Solvent rich, high solid, water borne paint, PC15: Solvent rich, high solid, water borne paint	---	Consumer inhalation, long term	93750mg/m ³	0.43
PC9a: Solvent rich, high solid, water borne paint, PC15: Solvent rich, high solid, water borne paint	---	Consumer dermal exposure	35.7mg/kg/day	0.00
PC9a: Solvent rich, high solid, water borne paint, PC15: Solvent rich, high solid, water borne paint	---	Consumer oral, long-term	0mg/kg/day	0.00
PC9a: Aerosol spray can, PC15: Aerosol spray can	---	Consumer inhalation, long term	32500mg/m ³	0.09
PC9a: Aerosol spray can, PC15: Aerosol spray can	---	Consumer dermal exposure	35.7mg/kg/day	0.00
PC9a: Aerosol spray can, PC15: Aerosol spray can	---	Consumer oral, long-term	0mg/kg/day	0.00
PC9a: Removers, PC15: Removers	---	Consumer inhalation, long term	90000mg/m ³	0.06
PC9a: Removers, PC15: Removers	---	Consumer dermal exposure	128.6mg/kg/day	0.00
PC9a: Removers, PC15: Removers	---	Consumer oral, long-term	0mg/kg/day	0.00
PC9b: Fillers and putty	---	Consumer inhalation, long term	50000mg/m ³	0.05
PC9b: Fillers and putty	---	Consumer dermal exposure	6mg/kg/day	0.00
PC9b: Fillers and putty	---	Consumer oral, long-term	0mg/kg/day	0.00
PC9b: Plasters and floor	---	Consumer inhalation, long term	> 999999mg/m ³	0.25

ISOPROPANOL 70-100%

equalizers				
PC9b: Plasters and floor equalizers	---	Consumer dermal exposure	142.9mg/kg/day	0.00
PC9b: Plasters and floor equalizers	---	Consumer oral, long-term	0mg/kg/day	0.00
PC9b: Modelling clay	---	Consumer inhalation, long term	0mg/m ³	0.00
PC9b: Modelling clay	---	Consumer dermal exposure	25.4mg/kg/day	0.01
PC9b: Modelling clay	---	Consumer oral, long-term	10mg/kg/day	0.77
PC9c: Finger paints	---	Consumer inhalation, long term	0mg/m ³	0
PC9c: Finger paints	---	Consumer dermal exposure	127.2mg/kg/day	0.12
PC9c: Finger paints	---	Consumer oral, long-term	68mg/kg/day	0.78
PC18: Refilling of toners	---	Consumer inhalation, long term	200mg/m ³	0.57
PC18: Refilling of toners	---	Consumer dermal exposure	1.2mg/kg/day	0.02
PC18: Refilling of toners	---	Consumer oral, long-term	0mg/kg/day	0.00
PC23: Polishes, wax/cream	---	Consumer inhalation, long term	1400mg/m ³	0.57
PC23: Polishes, wax/cream	---	Consumer dermal exposure	71.5mg/kg/day	0.11
PC23: Polishes, wax/cream	---	Consumer oral, long-term	0mg/kg/day	0.00
PC23: Polishes, spray	---	Consumer inhalation, long term	1400mg/m ³	0.20
PC23: Polishes, spray	---	Consumer dermal exposure	71.5mg/kg/day	0.11
PC23: Polishes, spray	---	Consumer oral, long-term	0mg/kg/day	0.00
PC24: Liquids	---	Consumer inhalation, long term	125000mg/m ³	0.04
PC24: Liquids	---	Consumer dermal exposure	71.5mg/kg/day	0.24
PC24: Liquids	---	Consumer oral, long-term	0mg/kg/day	0.00
PC24: Pastes	---	Consumer inhalation, long term	0mg/m ³	0.00
PC24: Pastes	---	Consumer dermal exposure	28.6mg/kg/day	0.05
PC24: Pastes	---	Consumer oral, long-term	0mg/kg/day	0.00
PC24: Sprays	---	Consumer inhalation, long term	7500mg/m ³	0.14
PC24: Sprays	---	Consumer dermal exposure	35.7mg/kg/day	0.11
PC24: Sprays	---	Consumer oral, long-term	0mg/kg/day	0.00
PC31: Polishes,	---	Consumer inhalation,	13750mg/m ³	0.12

ISOPROPANOL 70-100%

wax / cream		long term		
PC31: Polishes, wax / cream	---	Consumer dermal exposure	71.5mg/kg/day	0.01
PC31: Polishes, wax / cream	---	Consumer oral, long-term	0mg/kg/day	0.00
PC31: Polishes, spray	---	Consumer inhalation, long term	3375mg/m ³	0.12
PC31: Polishes, spray	---	Consumer dermal exposure	71.5mg/kg/day	0.11
PC31: Polishes, spray	---	Consumer oral, long-term	0mg/kg/day	0.00
PC34	---	Consumer inhalation, long term	575mg/m ³	0.40
PC34	---	Consumer dermal exposure	14.3mg/kg/day	0.00
PC34	---	Consumer oral, long-term	0mg/kg/day	0.00

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 9: Use in coatings

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC15: Use as laboratory reagent</p> <p>PROC19: Hand-mixing with intimate contact and only PPE available</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1)
	Filling/ preparation of equipment from drums or containers.	Handle substance within a closed system.(PROC2)
	General exposures (closed systems) Use in contained systems	Handle substance within a closed system.(PROC2)
	Manual Spraying Indoor	Carry out in a vented booth or extracted enclosure.(PROC11)
	Manual Spraying Outdoor	Ensure operation is undertaken outdoors.(PROC11)
	Dipping, immersion and pouring	Avoid manual contact with wet work pieces. Clear up spills immediately and dispose of waste

ISOPROPANOL 70-100%

	Indoor	safely.(PROC13)
	Dipping, immersion and pouring Outdoor	Avoid manual contact with wet work pieces. Clear up spills immediately and dispose of waste safely.(PROC13)
	Hand application - fingerpaints, pastels, adhesives Indoor	Ensure doors and windows are opened.(PROC19)
Conditions and measures related to personal protection, hygiene and health evaluation	Manual Spraying Outdoor	Wear a respirator conforming to EN140 with Type A filter or better.(PROC11)
	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15,
PROC19: ECETOC TRA worker v3

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	General exposures (closed systems)	Worker - inhalative, long-term	0.01ppm	0.00
PROC1	General exposures (closed systems)	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC2	General exposures (closed systems)	Worker - inhalative, long-term	20ppm	0.1
PROC2	General exposures (closed systems)	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00
PROC3	Preparation of material for application	Worker - inhalative, long-term	25ppm	0.1
PROC3	Preparation of material for application	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC4	Film formation - air drying	Worker - inhalative, long-term	50ppm	0.2
PROC4	Film formation - air drying	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.00
PROC5	Preparation of material for application	Worker - inhalative, long-term	100ppm	0.5
PROC5	Preparation of material for application	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.00
PROC8a	Material transfers	Worker - inhalative, long-term	100ppm	0.5
PROC8a	Material transfers	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.00
PROC8b	Drum/batch transfers	Worker - inhalative, long-term	50ppm	0.2
PROC8b	Drum/batch transfers	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.00
PROC10	Roller, spreader, flow	Worker - inhalative, long-term	100ppm	0.5

ISOPROPANOL 70-100%

	application	term		
PROC10	Roller, spreader, flow application	Worker - dermal, long-term - systemic	27.43mg/kg/day	0.00
PROC11	Manual spraying	Worker - inhalative, long-term	150ppm	0.7
PROC11	Manual spraying	Worker - dermal, long-term - systemic	107.14mg/kg/day	0.1
PROC13	Dipping, immersion and pouring	Worker - inhalative, long-term	100ppm	0.5
PROC13	Dipping, immersion and pouring	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.00
PROC15	Laboratory activities	Worker - inhalative, long-term	10ppm	0.00
PROC15	Laboratory activities	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC19	Hand application - fingerpaints, pastels, adhesives	Worker - inhalative, long-term	100ppm	0.5
PROC19	Hand application - fingerpaints, pastels, adhesives	Worker - dermal, long-term - systemic	141.43mg/kg/day	0.2

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 10: Use in cleaning agents

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Clear transfer lines prior to de-coupling.(PROC8a)
	Filling/ preparation of equipment from drums or containers.	Clear transfer lines prior to de-coupling.(PROC8b)
	Cleaning with high pressure washers	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).(PROC7)
Conditions and measures related to personal protection, hygiene and health evaluation	<p>Use suitable eye protection.</p> <p>Avoid direct eye contact with product, also via contamination on hands.</p>	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the

ISOPROPANOL 70-100%

Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 11: Use in cleaning agents

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC3: Air care products PC4: Anti-Freeze and de-icing products PC8: Biocidal products (e.g. Disinfectants, pest control) PC9a: Coatings and paints, thinners, paint removers PC24: Lubricants, greases, release products PC35: Washing and cleaning products PC38: Welding and soldering products (with flux coatings or flux cores.), flux products
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling consumer exposure for: PC3: Aircare, instant action (aerosol sprays)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.1 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	4 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC3: Aircare, continuous action (solid & liquid)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.48 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	480 min

ISOPROPANOL 70-100%

Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 35.7 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.4 Contributing scenario controlling consumer exposure for: PC4: Washing car window

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.5 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.5 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2000 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.6 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer

ISOPROPANOL 70-100%

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	4 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 214.4 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.7 Contributing scenario controlling consumer exposure for: PC8: Laundry and dish washing products

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	15 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	30 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.8 Contributing scenario controlling consumer exposure for: PC8: Cleaners, liquids

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	27 g
Frequency and duration of use	Frequency of use	128 days/year

ISOPROPANOL 70-100%

	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.9 Contributing scenario controlling consumer exposure for: PC8: Cleaners, trigger sprays

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.10 Contributing scenario controlling consumer exposure for: PC9a: Solvent rich, high solid, water borne paint

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 27,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	744 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428.75 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	

ISOPROPANOL 70-100%

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
--	-------------------	--

2.11 Contributing scenario controlling consumer exposure for: PC9a: Aerosol spray can

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	215 g
Frequency and duration of use	Frequency of use	2 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.12 Contributing scenario controlling consumer exposure for: PC9a: Removers (paint-, glue-, wall paper-, sealant-remover)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	491 g
Frequency and duration of use	Frequency of use	3 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.13 Contributing scenario controlling consumer exposure for: PC24: Liquids

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid

ISOPROPANOL 70-100%

	use)	
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2200 g
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.14 Contributing scenario controlling consumer exposure for: PC24: Pastes

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	34 g
Frequency and duration of use	Frequency of use	10 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.15 Contributing scenario controlling consumer exposure for: PC24: Sprays

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	73 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by	Exposed skin area	Covers skin contact area up to 428.75 cm ²

ISOPROPANOL 70-100%

risk management		
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.16 Contributing scenario controlling consumer exposure for: PC35: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	27 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.17 Contributing scenario controlling consumer exposure for: PC35: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

ISOPROPANOL 70-100%

protection and hygiene)

2.18 Contributing scenario controlling consumer exposure for: PC38

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	12 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

ECETOC TRA consumer v3. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 12: Use in cleaning agents

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC13: Treatment of articles by dipping and pouring</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Cleaning with high pressure washers Spraying Indoor	Provide a good standard of controlled ventilation (10 to 15 air changes per hour)(PROC11)
	Cleaning with high pressure washers Spraying Outdoor	Limit the substance content in the product to 1 %. or Avoid carrying out operation for more than 15 minutes. Ensure operation is undertaken outdoors.(PROC11)
Conditions and measures related to personal protection, hygiene and health evaluation	<p>Use suitable eye protection.</p> <p>Avoid direct eye contact with product, also via contamination on hands.</p>	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

ISOPROPANOL 70-100%

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 13: Use in binder and release agents

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC6: Calendering operations</p> <p>PROC7: Industrial spraying</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC10: Roller application or brushing</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC6, PROC7, PROC8b, PROC10, PROC14

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Material transfers	Clear transfer lines prior to de-coupling.(PROC1, PROC2, PROC3)
	Casting operations Open systems	Provide extraction ventilation at points where emissions occur.(PROC6)
	Spraying Machines	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Automate activity where possible.(PROC7)
	Spraying Manual	Carry out in a vented booth or extracted enclosure.(PROC7)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

ISOPROPANOL 70-100%

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 14: Use in binder and release agents

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC6: Calendering operations</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC6, PROC8b, PROC10, PROC11, PROC14, PROC1, PROC2, PROC3, PROC4

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Other operational conditions affecting workers exposure	Limit the substance content in the product to 25 %.(PROC6)	
Technical conditions and measures to control dispersion from source towards the worker	Material transfers Closed systems	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC1, PROC2, PROC3)
	Casting operations Open systems	Provide extraction ventilation at points where emissions occur.(PROC6)
	Spraying Machines	Minimise exposure by extracted full enclosure for the operation or equipment.(PROC11)
	Spraying Manual	Carry out in a vented booth or extracted enclosure.(PROC11)
	Batch process	Store substance within a closed system.(PROC1, PROC2)
Organisational measures to prevent /limit releases, dispersion and exposure	Spraying Machines	Segregate the activity away from other operations.(PROC11)
	Spraying Manual	Segregate the activity away from other operations.(PROC11)
Conditions and measures related to personal protection, hygiene	Spraying Manual	Wear a respirator conforming to EN140 with Type A/P2 filter or better.(PROC11)

ISOPROPANOL 70-100%

and health evaluation

Use suitable eye protection.
Avoid direct eye contact with product, also via contamination on hands.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 15: Use in agrochemicals

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC12: Fertilizers PC27: Plant protection products
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling consumer exposure for: PC12, PC27

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.3 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
		Covers use under typical household ventilation., Covers use at ambient temperatures.
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)		No specific risk management measure identified beyond those operational conditions stated.
	Consumer Measures	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

ECETOC TRA consumer v3. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 16: Use in agrochemicals

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC11: Non industrial spraying PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	< 4 hours/day(PROC11)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Other operational conditions affecting workers exposure	Limit the substance content in the product to 25 %.(PROC11)	
Technical conditions and measures to control dispersion from source towards the worker	Spraying/fogging by machine application	Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20.(PROC11)
	Operation of equipment containing engine oils and similar	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Disposal of wastes	Clear up spills immediately and dispose of waste safely.(PROC8a)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

ISOPROPANOL 70-100%

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 17: Use in fuel

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC16: Using material as fuel sources, limited exposure to unburned product to be expected
Environmental Release Categories	ERC7: Industrial use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC7

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Handle substance within a closed system. Clear transfer lines prior to de-coupling.(PROC8b)
	Drum/batch transfers	Avoid spillage when withdrawing pump. Use drum pumps or carefully pour from container.(PROC8b)
	General exposures (open systems) Closed systems	Handle substance within a closed system.(PROC1, PROC2)
	Equipment cleaning and maintenance	Apply vessel entry procedures including use of forced supplied air. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Drain down system prior to equipment break-in or maintenance.(PROC8a)
	Vessel and container cleaning	Apply vessel entry procedures including use of forced supplied air. Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system. Avoid dip sampling.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

ISOPROPANOL 70-100%

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 18: Use in fuel

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC13: Fuels
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b

2.2 Contributing scenario controlling consumer exposure for: PC13: Liquid: Automotive Refuelling

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	37500 g
Frequency and duration of use	Frequency of use	52 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	3 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 210 cm ²
Other given operational conditions affecting consumers exposure	Outdoor use	
	Room size	100 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC13: Liquid: Scooter Refuelling

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	3750 g
Frequency and duration of use	Frequency of use	52 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 210 cm ²
Other given operational conditions affecting consumers exposure	Outdoor use	
	Room size	100 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g.	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

ISOPROPANOL 70-100%

behavioural advice, personal protection and hygiene)

2.4 Contributing scenario controlling consumer exposure for: PC13: Liquid: Garden Equipment - Use

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	750 g
Frequency and duration of use	Frequency of use	26 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 420 cm ²
Other given operational conditions affecting consumers exposure	Outdoor use	
	Room size	100 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.5 Contributing scenario controlling consumer exposure for: PC13: Liquid: Garden Equipment - Refueling

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	750 g
Frequency and duration of use	Frequency of use	26 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 420 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.6 Contributing scenario controlling consumer exposure for: PC13: Liquid: home space heater fuel

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
-------------------------	---	---

ISOPROPANOL 70-100%

	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	750 g
Frequency and duration of use	Frequency of use	26 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 210 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.7 Contributing scenario controlling consumer exposure for: PC13: Liquid: Lamp oil

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	100 g
Frequency and duration of use	Frequency of use	52 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	0.6 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 210 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

ECETOC TRA consumer v3. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other risk management measures/operational conditions are adopted, then users should ensure that risks

ISOPROPANOL 70-100%

are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 19: Use in fuel

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC16: Using material as fuel sources, limited exposure to unburned product to be expected
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Handle substance within a closed system. Clear transfer lines prior to de-coupling.(PROC8b)
	Drum/batch transfers	Avoid spillage when withdrawing pump.(PROC8b)
	Refuelling aircraft	Avoid spillage when withdrawing pump.(PROC8a)
	General exposures (closed systems)	Handle substance within a closed system.(PROC3)
	General exposures (open systems) Closed systems	Handle substance within a closed system.(PROC16)
	Equipment cleaning and maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Vessel and container cleaning	Apply vessel entry procedures including use of forced supplied air. Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

ISOPROPANOL 70-100%

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 20: Use as lubricants

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC17: Lubrication at high energy conditions and in partly open process</p> <p>PROC18: Greasing at high energy conditions</p>
Environmental Release Categories	<p>ERC4: Industrial use of processing aids in processes and products, not becoming part of articles</p> <p>ERC7: Industrial use of substances in closed systems</p>

2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC7

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, PROC18

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	Bulk transfers	Clear transfer lines prior to de-coupling. Clear spills immediately. Remotely vent displaced vapours.(PROC8b)
	Operation and lubrication of high energy open equipment	Provide extract ventilation to points where emissions occur. Restrict area of openings to equipment.(PROC17, PROC18)
	Spraying	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Automate activity where possible. Clear transfer lines prior to de-coupling.(PROC7)
	Maintenance (of larger	Minimise exposure by partial enclosure of the

ISOPROPANOL 70-100%

	plant items) and machine set up	operation or equipment and provide extract ventilation at openings. Automate activity where possible.(PROC8b)
	Maintenance of small items	Avoid manual contact with wet work pieces. Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Remanufacture of reject articles	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC9)
	Storage	Store substance within a closed system. Avoid dip sampling.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Bulk transfers	Wear suitable gloves tested to EN374.(PROC8b)
		Wear suitable gloves tested to EN374.(PROC8b)
		Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 21: Use as lubricants

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC1: Adhesives, sealants PC24: Lubricants, greases, release products PC31: Polishes and wax blends
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d, ERC9a, ERC9b

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling consumer exposure for: PC1: Glues, hobby use

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	9 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC1: Glues DIY-use (carpet glue, tile glue, wood parquet glue)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	6390 g
Frequency and duration of use	Frequency of use	1 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 110 cm ²
Other given operational conditions affecting consumers	Room size	20 m3

ISOPROPANOL 70-100%

exposure	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.4 Contributing scenario controlling consumer exposure for: PC1: Glue from spray		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	85.05 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.5 Contributing scenario controlling consumer exposure for: PC1: Sealants		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	75 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.6 Contributing scenario controlling consumer exposure for: PC24: Liquids		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
R56871 / Version 7.0		
88/130		
EN		

ISOPROPANOL 70-100%

	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2200 g
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.7 Contributing scenario controlling consumer exposure for: PC24: Pastes

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	34 g
Frequency and duration of use	Frequency of use	10 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.8 Contributing scenario controlling consumer exposure for: PC24: Sprays

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	73 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min

ISOPROPANOL 70-100%

Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428.75 cm²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.9 Contributing scenario controlling consumer exposure for: PC31: Polishes, wax / cream (floor, furniture, shoes)		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	142 g
Frequency and duration of use	Frequency of use	29 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	73.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 430 cm²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.10 Contributing scenario controlling consumer exposure for: PC31: Polishes, spray (furniture, shoes)		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	8 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 430 cm²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
R56871 / Version 7.0		
90/130		
EN		

ISOPROPANOL 70-100%

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)

Consumer Measures

No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

ECETOC TRA consumer v3. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 22: Use as lubricants

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC17: Lubrication at high energy conditions and in partly open process</p> <p>PROC18: Greasing at high energy conditions</p> <p>PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC9a: Wide dispersive indoor use of substances in closed systems</p> <p>ERC9b: Wide dispersive outdoor use of substances in closed systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d, ERC9a, ERC9b

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, PROC18, PROC20

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	4 hours/day (PROC8a, PROC11, PROC17, PROC18)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system. (PROC1, PROC2, PROC3)
	Operation and lubrication of high energy open equipment Indoor	Restrict area of openings to equipment. Provide extraction ventilation at points where emissions occur. (PROC17, PROC18)
	Operation and lubrication of high energy open equipment Outdoor	Ensure operation is undertaken outdoors. (PROC17)

ISOPROPANOL 70-100%

	Maintenance (of larger plant items) and machine set up	Provide extract ventilation to emission points when contact with warm (>50oC) product is likely.(PROC8b)
	Maintenance of small items	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Spraying	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.(PROC11)
	Treatment by dipping and pouring	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Allow time for product to drain from workpiece.(PROC13)
	Treatment by dipping and pouring	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Allow time for product to drain from workpiece.(PROC13)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Maintenance of small items	Wear a respirator conforming to EN140 with Type A/P2 filter or better.(PROC8a)
	Spraying	Wear a respirator conforming to EN140 with Type A/P2 filter or better.(PROC11)
	Treatment by dipping and pouring	Wear a respirator conforming to EN140 with Type A/P2 filter or better.(PROC13)
	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 23: Use as Functional Fluids

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
Environmental Release Categories	ERC7: Industrial use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC7

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC9

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers Closed systems	Transfer via enclosed lines. Clear transfer lines prior to de-coupling.(PROC1, PROC2)
	Filling/ preparation of equipment from drums or containers.	Carefully pour from containers.(PROC8a)
	Remanufacture of reject articles	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC9)
	Equipment maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

ISOPROPANOL 70-100%

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 24: Use as Functional Fluids

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC16: Heat transfer fluids PC17: Hydraulic fluids
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling consumer exposure for: PC16, PC17

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2200 g
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
		Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m ³) under typical ventilation.
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

ECETOC TRA consumer v3. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 25: Use as Functional Fluids

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Transfer from/pouring from containers	Avoid spillage when withdrawing pump.(PROC9)
	Remanufacture of reject articles	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC9)
	Equipment maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the

ISOPROPANOL 70-100%

Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 26: Use in laboratories

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC10: Roller application or brushing PROC15: Use as laboratory reagent
Environmental Release Categories	ERC2: Formulation of preparations ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC2, ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC10, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	< 4 hours/day(PROC15)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Laboratory activities	Automate activity where possible. Restrict area of openings to equipment. Handle substance within a closed system. Clear spills immediately. Remotely vent displaced vapours. Use dedicated equipment.(PROC15)
	Cleaning	Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Automate activity where possible. Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).(PROC10)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

ISOPROPANOL 70-100%

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 27: Use in laboratories

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC10: Roller application or brushing PROC15: Use as laboratory reagent
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC10, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	< 4 hours/day(PROC15)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Laboratory activities	Handle substance within a closed system. Clear transfer lines prior to de-coupling. Clear spills immediately. Remotely vent displaced vapours. Use dedicated equipment. Restrict area of openings to equipment. Allow time for product to drain from workpiece. Automate activity where possible.(PROC15)
	Cleaning	Automate activity where possible. Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC10)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>

ISOPROPANOL 70-100%

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 28: Use in metal working fluids / rolling oils

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC17: Lubrication at high energy conditions and in partly open process</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	Bulk transfers	Clear transfer lines prior to de-coupling. Clear spills immediately. Remotely vent displaced vapours.(PROC8b)
	Process sampling	Use dedicated equipment.(PROC8b)
	Metal machining operations	Restrict area of openings to equipment.(PROC17)
	Treatment by dipping and pouring	Allow time for product to drain from workpiece. Automate activity where possible.(PROC13)
	Spraying	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Automate activity where possible.(PROC7)

ISOPROPANOL 70-100%

	Rolling, Brushing Manual	Avoid splashing.(PROC10)
	Semi-automated metal rolling/forming	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Automate activity where possible.(PROC17)
	Equipment cleaning and maintenance Dedicated facility	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8b)
	Equipment cleaning and maintenance Non-dedicated facility	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 29: Use in metal working fluids / rolling oils

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC17: Lubrication at high energy conditions and in partly open process</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	< 1 hours/day(PROC8a)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	Bulk transfers	Clear transfer lines prior to de-coupling.(PROC8b)
	Filling/ preparation of equipment from drums or containers. Dedicated facility	Clear transfer lines prior to de-coupling.(PROC8b)
	Metal machining operations	Provide enhanced general ventilation by mechanical means.(PROC17)
	Spraying	Provide enhanced general ventilation by mechanical means.(PROC11)
	Treatment by dipping and pouring	Allow time for product to drain from workpiece.(PROC13)
	Equipment cleaning and maintenance Non-dedicated facility	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Equipment cleaning and	Clear transfer lines prior to de-coupling.(PROC8b)

ISOPROPANOL 70-100%

	maintenance Dedicated facility	
	Storage	Handle substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Spraying	Wear a respirator conforming to EN140 with Type A/P2 filter or better.(PROC11)
	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 30: Use in de-icing and anti-icing applications

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC4: Anti-Freeze and de-icing products
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling consumer exposure for: PC4: Washing car window

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 1 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.5 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2000 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m3) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

ISOPROPANOL 70-100%

protection and hygiene)

2.4 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 40%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	4 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 214.4 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34 m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

ECETOC TRA consumer v3. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 31: Use in de-icing and anti-icing applications

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC11: Non industrial spraying
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC8a, PROC8b, PROC11

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	< 1 hours/day(PROC11)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Clear transfer lines prior to de-coupling.(PROC8b)
	Material transfers	Clear transfer lines prior to de-coupling.(PROC8b)
	Spraying/fogging by machine application	Ensure operation is undertaken outdoors.(PROC11)
Organisational measures to prevent /limit releases, dispersion and exposure	Spraying/fogging by machine application	Stay upwind/ keep distance from source.(PROC11)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

ISOPROPANOL 70-100%

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 32: Use as water treatment chemicals

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC3: Formulation in materials ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC3, ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Handle substance within a closed system. Clear transfer lines prior to de-coupling.(PROC2)
	Drum/batch transfers	Avoid spillage when withdrawing pump.(PROC8b)
	General exposures (open systems)	Restrict area of openings to equipment.(PROC4)
	Pouring from small containers	Use drum pumps or carefully pour from container.(PROC13)
	Batch process	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

ISOPROPANOL 70-100%

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 33: Use as water treatment chemicals

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC36: Water softeners PC37: Water treatment chemicals
Environmental Release Categories	ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

2.1 Contributing scenario controlling environmental exposure for: ERC8f

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling consumer exposure for: PC36

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	10 g
	Amount used per event (oral exposure)	0.000015 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 6600 cm²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC37

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	10 g
	Amount used per event (oral exposure)	0.000154 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin area	Covers skin contact area up to 6600 cm²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g.	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

ISOPROPANOL 70-100%

behavioural advice, personal protection and hygiene)

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

ECETOC TRA consumer v3. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 34: Use as water treatment chemicals

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

2.1 Contributing scenario controlling environmental exposure for: ERC8f

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC3, PROC4, PROC8a, PROC8b, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Drum/batch transfers	Avoid spillage when withdrawing pump. Clear transfer lines prior to de-coupling. Use drum pumps or carefully pour from container.(PROC8b)
	General exposures (open systems)	Restrict area of openings to equipment.(PROC4)
	Pouring from small containers	Carefully pour from containers. Avoid spillage when withdrawing pump.(PROC13)
	Equipment maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

ISOPROPANOL 70-100%

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 35: Use in oil and gas field drilling and production operations

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers from tote tanks and supply vessels	Handle substance within a closed system.(PROC8b)
	Filling/ preparation of equipment from drums or containers.	Handle substance within a closed system.(PROC8b)
	Drilling mud (re-)formulation	Handle substance within a closed system.(PROC3)
	Process sampling	Clear transfer lines prior to de-coupling. Clear spills immediately. Remotely vent displaced vapours.(PROC3)

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ISOPROPANOL 70-100%

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 36: Use in explosives

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact) PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Handle substance within a closed system. Clear transfer lines prior to de-coupling. Remotely vent displaced vapours.(PROC3)
	Transfer from/pouring from containers Non-dedicated facility	Avoid spillage when withdrawing pump.(PROC8a)
	Storage	Store substance within a closed system.(PROC1, PROC2)

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may

ISOPROPANOL 70-100%

be necessary to define appropriate site-specific risk management measures.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 37: Other consumer uses

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC28: Perfumes, fragrances PC39: Cosmetics, personal care products
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems
Activity	Note: this Exposure Scenario is only relevant for an appropriated use according to the quality grade of the substance delivered

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling consumer exposure for: PC28, PC39

Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 38: Use as an intermediate

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU8: Manufacture of bulk, large scale chemicals (including petroleum products) SU9: Manufacture of fine chemicals
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC15: Use as laboratory reagent
Environmental Release Categories	ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

2.1 Contributing scenario controlling environmental exposure for: ERC6a

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	General exposures (open systems)	Handle substance within a closed system.(PROC4)
	Bulk transfers Open systems	Handle substance within a closed system.(PROC8b)
	Bulk transfers Closed systems	Ensure material transfers are under containment or extract ventilation.(PROC8b)
	Equipment cleaning and maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle. Drain down system prior to equipment break-in or maintenance. Clear spills immediately.(PROC8a)
	Storage	Store substance within a closed system. Avoid dip sampling.(PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

ISOPROPANOL 70-100%

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15: ECETOC TRA worker v3

Contributing Scenario	Specific conditions	Exposure routes	Level of Exposure	RCR
PROC1	General exposures (closed systems)	Worker - inhalative, long-term	0.01ppm	0.00
PROC1	General exposures (closed systems)	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC2	General exposures (closed systems)	Worker - inhalative, long-term	10ppm	0.05
PROC2	General exposures (closed systems)	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00
PROC3	General exposures (closed systems)	Worker - inhalative, long-term	25ppm	0.12
PROC3	General exposures (closed systems)	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC4	General exposures (open systems)	Worker - inhalative, long-term	20ppm	0.10
PROC4	General exposures (open systems)	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC8b	Process sampling	Worker - inhalative, long-term	50ppm	0.25
PROC8b	Process sampling	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC15	Laboratory activities	Worker - inhalative, long-term	10ppm	0.05
PROC15	Laboratory activities	Worker - dermal, long-term - systemic	0.34mg/kg/day	0.00
PROC8b	Bulk transfers, Open systems	Worker - inhalative, long-term	150ppm	0.74
PROC8b	Bulk transfers, Open systems	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC8b	Bulk transfers, Closed systems	Worker - inhalative, long-term	2.5ppm	0.25
PROC8b	Bulk transfers, Closed systems	Worker - dermal, long-term - systemic	6.86mg/kg/day	0.01
PROC8a	Equipment cleaning and maintenance	Worker - inhalative, long-term	50ppm	0.25
PROC8a	Equipment cleaning and maintenance	Worker - dermal, long-term - systemic	13.71mg/kg/day	0.02
PROC2	Storage	Worker - inhalative, long-term	10ppm	0.05
PROC2	Storage	Worker - dermal, long-term - systemic	1.37mg/kg/day	0.00

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the

ISOPROPANOL 70-100%

Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 39: Use as blowing agents

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC12: Use of blowing agents in manufacture of foam
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Use vapour recovery units when necessary. Clear transfer lines prior to de-coupling.(PROC8b)
Organisational measures to prevent /limit releases, dispersion and exposure	Extrusion and expansion of polymer mass	Normal safe operations. Regular testing for fugitive emissions.(PROC12)

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>

ISOPROPANOL 70-100%

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 40: Use in road and construction applications

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC11: Non industrial spraying PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

2.1 Contributing scenario controlling environmental exposure for: ERC8d, ERC8f

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Other operational conditions affecting workers exposure	Operation is carried out at elevated temperature (> 20°C above ambient temperature).(PROC8b)	
Technical conditions and measures to control dispersion from source towards the worker	Drum/batch transfers Dedicated facility	Use dedicated equipment. Clear transfer lines prior to de-coupling.(PROC8b)
	Spraying/fogging by machine application	Automate activity where possible.(PROC11)
	Equipment cleaning and maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
Organisational measures to prevent /limit releases, dispersion and exposure	Spraying/fogging by machine application	Stay upwind/ keep distance from source.(PROC11)
Conditions and measures related to personal protection, hygiene and health evaluation	Drum/batch transfers Dedicated facility	Wear a respirator conforming to EN140 with Type A filter or better.(PROC8b)
	Spraying/fogging by machine application	Wear a respirator conforming to EN140 with Type A filter or better.(PROC11)

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ISOPROPANOL 70-100%

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 41: Use as mining chemicals

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)</p> <p>PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Handle substance within a closed system. Clear transfer lines prior to de-coupling.(PROC2)
	Drum/batch transfers	Avoid spillage when withdrawing pump.(PROC8b)
	Pouring from small containers	Handle all packages and containers carefully to minimise spills.(PROC9)
	Equipment cleaning and maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1)

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ISOPROPANOL 70-100%

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.