

**The Soap Kitchen (2011) Ltd**

Unit 8, Caddsdwn Industrial Park,  
Clovelly Road, Bideford, Devon,  
EX39 3DX, United Kingdom

Email: [enquiries@thesoapkitchen.co.uk](mailto:enquiries@thesoapkitchen.co.uk)

Call: +44 (0) 1237 420 872

## CERTIFICATE OF ANALYSIS

Despatch No. **23023 / 1**

Your Order No **Bill 09/07/2020**

Date despatched **29 July 2020**

Your code

Product name

Our code

CARAMEL FLAVOUR (DEV-50592)(EE220514A)

TF018421A 1x5 PK005

Batch	Units	Q/C
17989	1	Passed

Best before	DoM
29/04/2021	20/04/2020

**Shelf Life extensions**

Technical altered BBE date from 20/01/2021 to 29/04/2021

**Physical**

Organoleptic  
Refractive Index  
Visual  
Specific Gravity  
Sieve Mesh 1mm

**Results**

Pass  
1.4418  
Pass  
1.0491  
100% Pass

**Our Specification**

100% passes

Compliant to: Commission Regulation (EU) 1334/2008

Certificate issued 29/07/2020

**Legal Notice**

The information given in this publication is based on our current knowledge and experience, and may be used at your discretion and risk. It does not relieve you from carrying out your own precautions and tests. We do not assume any liability in connection with your product or its use. You must comply with all applicable laws and regulations, and observe all third party rights.

Microbiology results supplied are based upon our procedure code PPR 015 which is available upon request. This means that according to the designated level of risk, this batch may have been tested by our accredited Third Party lab, or the results may be based upon calculation and previous random sampling results.

Heavy Metals are tested by the company on a monitoring basis only unless expressly stated.

Shelf life dates given by Plant-ex are recommended according to studies carried out by the company over time, however they are not a warranty against natural degradation which may occur, particularly with Natural materials. Product strengths will be as stated at the time of delivery, thereafter it is the duty of the customer to store the material appropriately and use the material in a timely manner to avoid any loss in strength.