



The Soap Kitchen (2011) Ltd
Unit 8, Caddesdown Industrial Park, Clovelly Road,
Bideford, Devon, EX39 3DX, United Kingdom

Email: enquiries@thesoapkitchen.co.uk
Call: +44 (0) 1237 420 872

CERTIFICATE OF ANALYSIS

Despatch No. **20561 / 1**
Your Order No **BF 1001/2020**
Date despatched **05 February 2020**

Your code

Product name
PROSECCO FLAVOUR (DEV-50639)

Our code
TF018710A 1x3 PK005

| Batch | Units | Q/C | Best before | DoM |
|-------|-------|--------|-------------|------------|
| 16922 | 1 | Passed | 29/01/2021 | 29/01/2020 |

| Physical | Results | Our Specification |
|------------------|-----------|-------------------------|
| Organoleptic | Pass | Passes against standard |
| Refractive Index | 1.4316 | 1.421-1.441 |
| Visual | Pass | |
| Specific Gravity | 1.021 | 1.011-1.031 |
| Sieve Mesh 1mm | 100% Pass | 100% passes |

Certificate issued 05/02/2020

Legal Notice

The information given in this publication is based on our current knowledge and experience, and may be used at your discretion and risk. It does not relieve you from carrying out your own precautions and tests. We do not assume any liability in connection with your product or its use. You must comply with all applicable laws and regulations, and observe all third party rights.

Microbiology results supplied are based upon our procedure code PPR 015 which is available upon request. This means that according to the designated level of risk, this batch may have been tested by our accredited Third Party lab, or the results may be based upon calculation and previous random sampling results.

Heavy Metals are tested by the company on a monitoring basis only unless expressly stated.

Shelf life dates given by Plant-ex are recommended according to studies carried out by the company over time, however they are not a warranty against natural degradation which may occur, particularly with Natural materials. Product strength will be as stated at the time of delivery, thereafter it is the duty of the customer to store the material appropriately and use the material in a timely manner to avoid any loss in strength.